




30V_{DS}/±20V_{GS} N-Channel Enhancement Mode MOSFET

Features

- V_{DS}=30V, I_D=400A
- R_{DS(ON)}=0.65mΩ (TYP.) V_{GS}=10V, I_D=20A
- R_{DS(ON)}=1mΩ (TYP.) V_{GS}=4.5V, I_D=20A
- Reliable and Rugged
- Avalanche Rated
- Low On-Resistance
- Halogen and Antimony Free, Rohs compliant

PDFN5060



Applications

- Load Switch
- Power management in portable/desktop PCs
- DC/DC conversion

Ordering Information

| Orderable Device | Package | Marking Information | Package Qty. |
|------------------|----------|----------------------|--------------|
| AER3Z51AE | PDFN5060 | AER3Z51AE ywwFxxx | 5000pcs/Reel |

Absolute Maximum Ratings (T_C=25°C, unless otherwise noted)

| Parameter | Symbol | Value | Unit |
|---|-----------------------------------|---------|------|
| Drain-Source Voltage | V _{DS} | 30 | V |
| Gate-Source Voltage | V _{GS} | ±20 | V |
| Continuous Drain Current (T _C =25°C) | I _D | 400 | A |
| Continuous Drain Current (T _C =100°C) | | 280 | A |
| Pulsed Drain Current | I _{DM} | 1200 | A |
| Avalanche Current (L=0.1mH) | I _{AS} | 138 | A |
| Single Pulsed Avalanche Energy | E _{AS} | 950 | mJ |
| Maximum Power Dissipation (T _C =25°C) | P _D | 250 | W |
| Maximum Power Dissipation (T _C =100°C) | | 100 | W |
| Operating, Storage Temperature Range | T _J , T _{STG} | -55~175 | °C |

Thermal Characteristics

| Parameter | Symbol | Min. | Typ. | Max. | Unit |
|---|------------------|------|------|------|------|
| Thermal Resistance, Junction-to-Case | R _{θJC} | - | 0.5 | - | °C/W |
| Thermal Resistance, Junction-to-Ambient | R _{θJA} | - | 41 | - | °C/W |



Electrical Characteristics

| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|----------------------------------|--------------|-------------------------------|------|------|-----------|------------|
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=250\mu A$ | 30 | - | - | V |
| Zero Gate Voltage Drain Current | I_{DSS} | $V_{DS}=30V, V_{GS}=0V$ | - | - | 1 | μA |
| Gate -Source Leakage Current | I_{GSS} | $V_{GS}=\pm 20V, V_{DS}=0V$ | - | - | ± 100 | nA |
| Gate Threshold Voltage | $V_{GS(th)}$ | $V_{DS}=V_{GS}, I_D=250\mu A$ | 1.0 | 1.8 | 2.5 | V |
| Drain-Source On-stage Resistance | $R_{DS(on)}$ | $V_{GS}=10V, I_D=20A$ | - | 0.65 | 0.85 | m Ω |
| | | $V_{GS}=4.5V, I_D=20A$ | - | 1.0 | 1.3 | |

Dynamic Characteristics


| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|------------------------------|--------------|-----------------|------|------|------|----------|
| Input capacitance | C_{iss} | $V_{DS}=15V$ | - | 8772 | - | pF |
| Output capacitance | C_{oss} | $V_{GS}=0V$ | - | 3043 | - | |
| Reverse transfer capacitance | C_{rss} | $f=1MHz$ | - | 188 | - | |
| Gate Resistance | R_g | $f=1MHz$ | - | 2.3 | - | Ω |
| Total Gate Charge | Q_g | $V_{DS}=15V$ | - | 110 | - | nC |
| Gate Source Charge | Q_{gs} | $V_{GS}=10V$ | - | 13 | - | |
| Gate Drain Charge | Q_{gd} | $I_D=20A$ | - | 22 | - | |
| Turn-on delay Time | $t_{d(on)}$ | $V_{GS}=10V$ | - | 16 | - | ns |
| Rise time | t_r | $V_{DS}=15V$ | - | 15 | - | |
| Turn-off delay Time | $t_{d(off)}$ | $I_D=20A$ | - | 70 | - | |
| Fall time | t_f | $R_G=3\Omega$ | - | 25 | - | |






Reverse Diode Characteristics

| Parameter | Symbol | Test Conditions | Min. | Typ. | Max. | Unit |
|----------------------------|----------|-------------------------|------|------|------|------|
| Body Diode Forward Voltage | V_{SD} | $V_{GS}=0V, I_{SD}=1A$ | - | 0.7 | 1.2 | V |
| Reverse Recovery Time | t_{rr} | $V_{GS}=0V, I_{SD}=20A$ | - | 35 | - | ns |
| Reverse Recovery Charge | Q_{rr} | $d_i/d_t=500A/\mu s$ | - | 112 | - | nC |



Electrical Characteristics Diagrams









Physical Dimensions

PDFN5060



| SYMBOLS | DIMENSIONS IN MILLIMETERS | | |
|---------|---------------------------|-------|-------|
| | MIN | NOM | MAX |
| A | 0.85 | 0.95 | 1.10 |
| A1 | 0.00 | - | 0.05 |
| b | 0.30 | 0.40 | 0.50 |
| c | 0.15 | 0.20 | 0.25 |
| D | 4.80 | 5.10 | 5.40 |
| D1 | 4.25 | 4.35 | 4.45 |
| E | 5.50 | 5.75 | 6.00 |
| E1 | 5.95 | 6.05 | 6.25 |
| E2 | 3.525 | 3.625 | 3.725 |
| E3 | 1.175 | 1.275 | 1.375 |
| e | 1.27BSC | | |
| L | 0.45 | 0.55 | 0.65 |
| L1 | 0.00 | - | 0.15 |
| L2 | 0.68REF | | |
| θ | 0° | - | 10° |

< Copyright >

All the Patent, Copyright and IP contained in this document belong to ALE, shall not be reproduced, copied, or used in other ways without permission.